

Cabinets, Racks and Accessories

Floor Standing Server Cabinets - SSRS 19"

01



Floor Standing Server Cabinets SSRS

Features:

- sheet steel housing with welded frame, completely pre-assembled,
- possibility of controlling ventilating air flow by application of proper type of fans, door, side and rear panels,
- protection IP20 in accordance with PN 92/E-08106 / EN 60 529 / IEC 529. (does not apply to brush cable entries),
- cabinets can be arranged in array using line-up bolts (Article No.ZLS-B),
- cabinet frame fully welded - 1,5 mm thick sheet steel on 4 x leveling feet M10,
- front door: with window made of safety glass (optionally: full steel, full glass, punched perforated plate), opening angle 180 degrees, with three point turning handle with latch, lockable. Left or right opening options,
- cabinet rear panel - 1 mm thick sheet steel, removable with two single point locks
- cabinet side panels - 1 mm thick sheet steel, removable with two single point locks.
- two pairs of mounting rails (AL-Zn coated) each arranged at the front and rear on the inside. Each profile with unit labeling. new profile fixing system efficiently increase maximum load capacity of the cabinets and facilitates cables management.
- profile rails with 25 mm. hole spacing arranged horizontally at the top and the bottom of the cabinet, for fixing and depth adjustment of the profile rails.
- available with front swing frame 19" mounting profiles.
- cables let in entry optionally either from roof or base, either through top or bottom of the rear side of cabinet, pre-punched opening.
- in the roof and base of cabinet 2 x 4U blind plates (pre-punched opening) for fan units (possible configurations 1 or 2 x 2 fan units, 1 x 4 fan units, 1 x 6 fan units).
- possibility to increase maximum weight of equipment mounted in the cabinet by using cabinet max load strengthening kit.
- wide range of supplementary accessories : plinths, shelves, fan units, light units, power distribution units, blanking covers,

Version	Type	Dimensions (mm)			Weight (kg)	Load capacity (kg)	Index
		Width	Depth	Height			
BOX							
	42U	600	1000	1980	116,1	600	SSRS-42-6/10-BOX-G
		800	1000		139,0		SSRS-42-8/10-BOX-G
		800	1000	2120	143,9		SSRS-45-8/10-BOX-G
ICE							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-ICE-G
STANDARD II							
	42U	600	1000	1980	139,0	600	SSRS-42-6/10-S02-G
		800	1000		159,0		SSRS-42-8/10-S02-G
		800	1200	139,0	SSRS-42-8/12-S02-G		
STANDARD III							
	42U	600	1000	1980	139,0	600	SSRS-42-6/10-S03-G
		800	1200		159,0		SSRS-42-8/12-S03-G
TOP II							
	42U	600	1000	1980	116,1	600	SSRS-42-6/10-T02-G
		800	1000		139,0		SSRS-42-8/10-T02-G
		800	1200	159,0	SSRS-42-8/12-T02-G		
TOP III							
	42U	600	1000	1980	116,1	600	SSRS-42-6/10-T03-G
		800	1000		139,0		SSRS-42-8/10-T03-G
		800	1200	159,0	SSRS-42-6/12-T03-G		
WEST							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W01-G
WEST-B							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W01-B
WEST II							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W02-G
WEST II-B							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W02-B
WEST III							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W03-G
WEST III-B							
	42U	800	1000	1980	139,0	600	SSRS-42-8/10-W03-B

Cabinets, Racks and Accessories

Floor Standing Server Cabinets - SSRS 19"



01

Floor Standing Server Cabinets SSRS



- **BOX** - Metal front door with window made of safety glass with three point lock, rear - full meta panel or door with two single point locks, standard color powder painted in RAL 7035 - light grey.
- **ICE** - Full safety glass front door with two single point locks, rear - full metal panel or door with two single point locks, standard color powder painted in RAL 7035 - light grey.

- **STANDARD II** - perforated front door and perforated rear panel, RAL 7035 grey, new perforation 80%
- **STANDARD III** - Perforated front and back door (same height), RAL 7035 grey, new perforation 80%
- **TOP II** - Perforated front door and perforated rear panel, RAL 7021 black, new perforation 80%.
- **TOP III** - Perforated front and back door (same height), RAL 7021 black, new perforation 80%.



- **WEST** - Perforated front and back double door (same height), RAL 7035 grey, new perforation 80%.
- **WEST-B** - Perforated front and back double door (same height), RAL 7021 black, new perforation 80%.
- **WEST II** - Perforated, double front door; perforated short rear panel, RAL 7035 black, new perforation 80%.
- **WEST II-B** - Perforated front and back double door (same height), RAL 7021 black, new perforation 80%.
- **WEST III** - Double front door metal/glass; sheet steel rear panel, RAL 7035 grey.
- **WEST III-B** - Double front door metal/glass; sheet steel rear panel, RAL 7021 black.

Accessories supplied:

- 1 x brush terminal,
- 1 x set of captive nuts (16 pcs.),
- 2 x keys for sides and rear panels,
- 2 x keys for front door,
- 4 x leveling feet M10,
- 1,5m of cable entry cover for cables protection (after removing cable entry).